Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

modern seamless surface

EMCO

1.	Product and company identification	
1.1	Identification of the substance or preparation:	
	Commercial product name:	COLOR GRAIN
	Use of substance / preparation	Industrial. Modifying agent for: Building materials
1.2	Company/undertaking identification:	
	Manufacturer/distributor:	SEMCO Modern Seamless Surface Inc 3620 West Reno Avenue Las Vegas, NV 8118 USA
	Customer information:	InfoLine: Tel (702) 222-9495, info@semcosurfaces.com Hours of operation: Monday - Friday,8 am to 5 pm (pacific standard time) Corporate website: www.semcosurfaces.com
	Emergency telephone no. (24h): Transportation emergency:	(800) 424-9300 (CHEMTREC, USA) (703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Product Safety Department (RAPS) of SEMCO Modern Seamless Surface Inc.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Class	Category	Route of
		exposure
Serious eye damage / eye irritation	Category 2	

2.2 Label elements

Labelling (GHS):

Pictogram(s):



Signal Word: Warning

H-Code	Hazard Statements
H315+H320	Causes skin and eye irritation.
P-Code	Precautionary Statements
P103	Read label before use.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.
P404	Store in a closed container.
P501	Dispose of contents/container to waste disposal.

Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

2.3 Other hazards

No data available.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics

Polysiloxane with functional groups + Fluoropolymer + organosilane (dispersion in water)

3.2 Information on ingredients:

Туре	CAS No.	Substance	Content	[wt. %]	Note
			Lower	Upper	
INHA	2867-47-2	Proprietary Monomer		<=2.347	

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product.

4. First-aid measures

4.1 General information:

Get medical attention if irritation occurs or if breathing becomes difficult. Remove contaminated clothing and shoes.

4.2 After inhalation

If inhaled remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen.

4.3 After contact with the skin

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

For ingestion, if conscious, give several glasses of water but do not induce vomiting. If vomiting does occur, give additional fluids.

4.6 Advice for the physician

Treat symptomatically.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:
Flash point	> 93 °C (> 199 °F)
Boiling point / boiling range Lower explosion limit (LEL): Upper explosion limit (UEL) Ignition temperature NEPA Hazard Class (comb /flam liquid)	not determined not determined not determined not determined

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

Method: (ASTM D3278, DIN 55680, ISO 3679)

Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

Date of print: 02/20/2017

modern seamless surface

5.3 Recommended extinguishing media:

carbon dioxide, dry sand, dry chemical or foam-type extinguishing media Water may be used to cool tanks and structures adjacent to the fire.

5.4 Unsuitable extinguishing media:

None.

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon monoxide , carbon dioxide , silicon dioxide , formaldehyde , Various hydrocarbon fragments .

5.6 Fire fighting procedures:

Full turn-out gear and Self Contained Breathing Apparatus (SCBA) should be worn when fighting large fires.

6. Accidental release measures

6.1 Precautions:

Wear personal protection equipment (see section 8). Avoid contact with eyes and skin. Avoid inhaling mists and vapours. If material is released indicate risk of slipping.

HAZWOPER PPE Level: C

6.2 Containment:

Prevent material from entering sewers or surface waters. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations. Contain larger amounts and pump up into suitable containers. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner.

6.4 Further information:

Eliminate all sources of ignition.

7. Handling and storage

7.1 General information:

Avoid exposure by technical measures or personal protective equipment. Always stir well before use.

7.2 Handling

Precautions for safe handling:

Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Avoid breathing dust/vapor/mist/gas/aerosol. Keep container closed when not in use. When transferring flammable liquids between metal containers, ground and bond the containers to drain off and equalize their static electric charges and reduce the potential for static sparks to occur.

Precautions against fire and explosion:

Do not weld, cut, or grind on empty containers. Where feasible maintain the temperature of flammable or combustible liquids at least 30° F below their flash point. Flammable, combustible or explosive air-vapor mixtures may be present in partial or uncleaned empty containers.

7.3 Storage

Conditions for storage rooms and vessels:

Do not store flammable liquids in plastic IBCs (i.e. Intermediate Bulk Containers or plastic tote tanks). Protect against frost.

Advice for storage of incompatible materials:

none known .

Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

Date of print: 02/20/2017

Method:

(ASTM D3278, DIN 55680, ISO 3679)

modern seamless surface

Further information for storage:

Protect against sun. Keep container tightly closed and store in a cool, well ventilated place. Protect against frost. **Minimum temperature allowed during storage and transportation:** 0 °C (32 °F) Do not allow this material to freeze. **Maximum temperature allowed during storage and transportation:** 50 °C (122 °F)

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

If spraying or other aerosol generating operations are performed, local exhaust ventilation designed to capture mists and sprays, such as a paint spray booth, is recommended.

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

CAS No.	Material	Туре	mg/m³	ppm	Dust fract.
64-19-7	Acetic acid	OSHA PEL	25.0	10.0	
64-19-7	Acetic acid	ACGIH TWA		10.0	

Re Acetic acid (CAS-no. 64-19-7): STEL is 15 ppm (ACGIH).

none known

8.3 Personal protection equipment (PPE)

Respiratory protection:

If spraying or other operations which generate an aerosol mist are conducted, respiratory protection for exposed personnel is recommended. A NIOSH approved air purifying respirator equipped with universal multi-contaminant, multi-gas/vapor cartridges and at least P-99 solid/aerosol particulate filters is recommended if overexposure to dusts, mists, or vapors could occur.

Hand protection:

Any liquid-tight rubber or vinyl gloves.

Eye protection:

Safety glasses with side shields or chemical safety goggles.

Other protective clothing or equipment:

Additional skin protection, such as SARANEX coated Tyvek apron, over-sleeves, lab coat, coveralls, or protective suit should be worn if splashing could occur. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Follow standard industrial hygiene practices when using this material. When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

9.2 Safety parameters

Property:	Value:
Melting point / melting range:	not determined
Boiling point / boiling range	not determined
Flash point	> 93 °C (> 199 °F)
Ignition temperature	not determined

SEMCO modern seamless surface

Safety Data Sheet

Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

Lower explosion limit (LEL):	not determined
Upper explosion limit (UEL):	not determined
Vapour pressure:	not determined
Density:	1.05 g/cm ³ at 23 °C (73 °F), at 1015 hPa
Water solubility / miscibility:	completely miscible
pH-Value	4.5 at 23 °C (73 °F) (1000 g/l H ₂ O)
Viscosity (dynamic)	55 mPa.s at 23 °C (73 °F)
Eurther information	33 m a.s at 23 °C (73 °F)

9.3 Further information

Corrosive to Steel or Aluminum...... Not corrosive to steel or aluminum.

10. Stability and reactivity

10.1 General information:

Stable under normal conditions of use. If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

Although this product is not expected to react with commonly used materials of construction and process equipment, it is advised that any rubber or plastic items such as hoses and gaskets be tested prior to large scale processing to ensure there is no degradation of performance or durability. Heat, open flames, and other sources of ignition. Protect against frost.

10.3 Materials to avoid

Reacts with: acids and alkalis . Reaction causes the formation of: ethanol , methanol .

10.4 Hazardous decomposition products

By hydrolysis: ethanol , methanol . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 General information

Data derived for the product as a whole are of higher priority than data for single ingredients.

11.1.2 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product. No data on acute inhalation toxicity is available for this product. In case of aerosol formation: Avoid inhalative exposure!

Acute toxicity estimate (ATE):

ATE_{mix} (oral): > 2000 mg/kg

11.1.3 Skin corrosion/irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.4 Serious eye damage / eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Material: 20071922

COLOR GRAIN

Version: 2.5 (US)

OR GRAIN

Date of last alteration: 04/11/2016

modern

Data related to ingredients:

5-Chloro-2-methyl-4-isothiazoline-3-on and 2-methyl-4-isothiazoline-3-on (mixture in a ratio of 3:1):

Based on the proven low sensitization induction threshold in human, mixtures containing ≥15 ppm are classified as skin sensitizing in Europe.

Date of print: 02/20/2017

11.1.6 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.12 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Data related to ingredients:

Product of hydrolysis (Methanol):

Methanol (CAS 67-56-1) is readily and rapidly absorbed at all exposure routes and is toxic by all routes. Methanol may cause irritation of the mucosa, as well as nausea, vomiting, headaches, vertigo and visual disorders, including blindness (irreversible damage to the optic nerve), acidosis, spasms, narcosis and coma. There may be a delay in the onset of these effects after exposure.

12. Ecological information

12.1 Toxicity

Assessment:

For the product as a whole, no test data is available.

12.2 Persistence and degradability

Assessment:

For the product as a whole, no test data is available.

Data related to ingredients:

Material: 20071922

Version: 2.5 (US)

COLOR GRAIN

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

Product of hydrolysis (Methanol):

The product of hydrolysis (methanol) is readily biodegradable.

12.3 Bioaccumulative potential

Assessment:

No data known.

12.4 Mobility in soil

Assessment:

No data known.

12.5 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator. Observe local/state/federal regulations.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Other Information	Not regulated for transport Protect from freezing, when exposed to cold temperatures approaching 0 $^\circ\text{C}$ (32 $^\circ\text{F})$ or below.

14.2 Transport by sea IMDG-Code

Valuation Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and **TSCA** information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory. This material or its component(s) is in compliance with TSCA under a Low Volume Exemption.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

64-19-7 Acetic acid 5,000 lbs	<=1.4088

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

Delayed (chronic) health hazard.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

Material: 20071922

Version: 2.5 (US)

COLOR GRAIN

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

HAPS (Hazardous Air Pollutants):

This material does not contain any HAPS substances

15.2 U.S. State regulations

California Proposition 65 Carcinogens:

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

67-56-1 Methanol

Massachusetts Substance List:

64-19-7Acetic acid2867-47-2Proprietary Monomer

New Jersey Right-to-Know Hazardous Substance List:

64-19-7Acetic acid2867-47-2Proprietary Monomer

Pennsylvania Right-to-Know Hazardous Substance List:

64-19-7Acetic acid57-55-6Propylene glycol2867-47-2Proprietary Monomer

15.3 Canadian regulations

This product has been classified in accordance with the Hazard criteria of the CPR and the SDS contains all the information required by the CPR.

WHMIS Hazard Classes:

None.

DSL Status:

This material or one or more of its components is not listed on the Canadian Domestic Substances List.

Non-DSL Chemicals:

CAS No.	CAS No. Chemical	
Confidential	Vendor Trade Secret Polymer (Not Disclosed, Proprietary, Unknown)	<= 9.388

15.4 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

European Economic Area (EEA).....: REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

16. Other information

16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

Material:	20071922
matorian	

Version: 2.5 (US)

COLOR GRAIN

Date of print: 02/20/2017

Date of last alteration: 04/11/2016

All deliveries are subject to the SEMCO Health Care Policy.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial	ppm - Parts per Million
Hygienists	SARA - Superfund Amendments and Reauthorization Act
DOT - Department of Transportation	STEL - Short Term Exposure Limit
hPa - Hectopascals	TSCA - Toxic Substances Control Act
mPa*s - Milli Pascal-Seconds	TWA - Time Weighted Average
OSHA - Occupational Safety and Health Administration	WHMIS - Canadian Workplace Hazardous Materials
PEL - Permissible Exposure Limit	Identification System
Flash point determination methods ASTM D56 ASTM D92, DIN 51376, ISO 2592 ASTM D93, DIN 51758, ISO 2719 ASTM D3278, DIN 55680, ISO 3679 DIN 51755	Common name Tagliabue (Tag) closed cup Cleveland open cup Pensky-Martens closed cup Setaflash or Rapid closed cup Abel-Pensky closed cup

16.3 Conversion table:

Pressure:	1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:	1 mPa*s = 1 centipoise (cP)