

SAFETY DATA SHEET

Page 1 of 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

SEMCO MODERN SEAMLESS SURFACE INC
3620 W. RENO AVE SUITE J
LAS VEGAS, NV 89118

TRADE NAME: XTRA GLOSS
COLOR: SEMI CLEAR
MAIN USE: HIGH TRAFFIC FLOOR SEALER

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER!
HARMFUL OR FATAL IF SWALLOWED
HARMFUL IF INHALED
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION
RESPIRATORY TRACT, SKIN, NERVOUS SYSTEM, EYE, LENS OR CORNEA
FLAMMABLE LIQUID AND VAPOR
VAPOR MAY CAUSE FLASH FIRE
MAY BE HARMFUL IF ABSORBED THROUGH SKIN

PRIMARY ROUTES OF ENTRY: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)

EYES:

ACUTE – LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. IF LEFT UNTREATED, CORNEAL DAMAGE CAN OCCUR AND INJURY IS SLOW TO HEAL. HOWEVER, DAMAGE IS USUALLY REVERSIBLE

CHRONIC – PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS

SKIN CONTACT:

ACUTE – REPEATED OR PROLONGED SKIN CONTACT CAN RESULT IN DRY, DEFATTED AND CRACKED SKIN CAUSING INCREASED SUSCEPTIBILITY TO INFECTION. IN ADDITION IRRITATION MAY DEVELOP INTO DERMATITIS. SOLVENTS CAN PENETRATE THE SKIN AND MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER ACUTE INHALATION SYMPTOMS.

CHRONIC – MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER CHRONIC INHALATION EFFECTS.

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

INHALATION:

ACUTE – SOLVENT VAPORS ARE IRRITATING TO THE EYES NOSE AND THROAT. SYMPTOMS OF IRRITATION MAY INCLUDE RED, ITCHY EYES, DRYNESS OF THE THROAT AND A FEELING OF TIGHTNESS IN THE CHEST. OTHER POSSIBLE SYMPTOMS OF OVEREXPOSURE INCLUDE: HEADACHE, DIZZINESS, NAUSEA, NARCOSIS FATIGUE AND LOSS OF APPETITE. PERSONS EXPOSED TO 200 PPM OF XYLENE EXPERIENCED EYE, NOSE AND THROAT IRRITATION. CONCENTRATIONS OF 10,000 PPM OF XYLENE CAN BE IMMEDIATELY DANGEROUS TO LIFE AND HEALTH

SAFETY DATA SHEET

SECTION 2: HAZARDS IDENTIFICATION (CON'T)

INHALATION:

CHRONIC – CHRONIC EXPOSURE TO ORGANIC SOLVENTS HAS BEEN ASSOCIATED WITH VARIOUS NEUROTOXIC EFFECTS INCLUDING PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. SYMPTOMS INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

INGESTION:

ACUTE – CAN RESULT IN IRRITATION OF THE DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT ABDOMINAL PAIN NAUSEA, VOMITING AND DIARRHEA. VOMITING MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEMICAL PNEUMONITIS

CHRONIC – ND

CONDITIONS AGGRAVATED BY EXPOSURE: SKIN DISORDERS AND ALLERGIES.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	Wt. %	CAS Number
XYLENE-MIXED ORTHO, META AND PARA ISOMERS	15-40	001330-20-7
ACETONE	7-15	000067-64-1

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 20°C (-4°F) TCC (ACETONE)

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: (ACETONE) **LEL:** 2.6% **UEL:** 12.8%

OSHA CLASS: FLAMMABLE LIQUID, PACKING GROUP II

AUTO IGNITION TEMP: 465°C (869°F)

SENSITIVITY TO IMPACT: ND

SENSITIVITY TO STATIC DISCHARGE: ND

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER SPRAY IS USEFUL IN COOLING FIRE-EXPOSED VESSELS AND IN DISPERSING VAPORS.

SAFETY DATA SHEET

SECTION 5: FIRE FIGHTING MEASURES CON'T.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT. SOLVENT VAPORS MAY BE HEAVIER THAN AIR. UNDER CONDITIONS OF STAGNANT AIR, VAPORS MAY BUILD UP AND TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE.

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT. USE NON-SPARKING TOOLS AND GROUNDING CABLES WHEN TRANSFERRING. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY.

STORAGE: AVOID TEMPERATURE EXTREMES. STORE AWAY FROM EXCESSIVE HEAT, FROM SOURCES OF IGNITION AND FROM REACTIVE MATERIALS. MATERIAL CAN BURN; LIMIT INDOOR STORAGE TO AREAS EQUIPPED WITH AUTOMATIC SPRINKLERS. STORE OUT OF DIRECT SUNLIGHT IN A COOL PLACE. KEEP CONTAINERS TIGHTLY CLOSED. GROUND ALL METAL CONTAINERS DURING STORAGE AND HANDLING.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS (ppm)

INGREDIENTS (CAS)	OSHA		ACGIH		OTHER
	TWA	STEL	TWA	STEL	
001330-20-7	100	150	100	150	
000067-64-1	750	NE	750	NE	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATION OF THE SOLVENTS BELOW THEIR RESPECTIVE TLV'S. EXHAUST AIR MAY NEED TO BE CLEANED BY SCRUBBERS OR FILTERS TO REDUCE ENVIRONMENTAL CONTAMINATION.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SAFETY DATA SHEET

Page 4 of 5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 56.2°C (133.2°F) (ACETONE)	SPECIFIC GRAVITY: 0.95-1.05
VAPOR PRESSURE: 180mm Hg (ACETONE)	MELTING POINT: ND
VAPOR DENSITY: 2.0 (AIR = 1)	EVAPORATION RATE: >2 (XYLENE = 2)
SOLUBILITY IN WATER: INSOLUBLE	pH: NA
COEFFICIENT of WATER/OIL DISTRIBUTION: ND	ODOR THRESHOLD: ND
APPEARANCE AND ODOR: CLEAR TO HAZY LIQUID, SWEET SOLVENT ODOR	
% VOLATILES BY VOLUME: 62%	%SOLIDS BY WEIGHT: 46%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE;

CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE)

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PERCHLORATES, NITRATES), STRONG ACIDS, HYPOCHLORITES, PEROXIDES.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

CARCINOGENIC DATA: THIS PRODUCT CONTAINS XYLENE, ETHYLBENZENE IN CONCENTRATIONS OF 0.1% OR GREATER.

TERATOGENICITY: YES	MUTAGENICITY: ND
EMBRYOTOXICITY: ND	SYNERGISTIC MATERIAL: ND

OVEREXPOSURE EFFECTS: LACRIMATION OF EYES, SKIN IRRITATION, DIZZINESS.

IRRITANCY: YES
SENSITIZER: YES

ACUTE TOXICITY EFFECTS: ORAL LD₅₀: 11.4g/kg (Rats); DERMAL LD₅₀: >20ml/kg (Rabbit); INHALATION: ND

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: NOT READILY BIODEGRADABLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. RCRA CLASSIFIED HAZARDOUS WASTE WITH CHARACTERISTIC OF IGNITABILITY.

SAFETY DATA SHEET

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: UN1263, FLAMMABLE, PAINT RELATED MATERIALS, 3, PG III
PACKAGING GROUP: III **DOT PRODUCT RQ LBS (KGS):** 800 LBS. (362.9 KGS)
HAZARD LABEL: FLAMMABLE LIQUID **HAZARD PLACARD:** FLAMMABLE LIQUID
IMO SHIPPING DATA: UN1263, FLAMMABLE, PAINT RELATED MATERIALS, 3, PG III
ICAO/IATA SHIPPING DATA: UN1263, FLAMMABLE, PAINT RELATED MATERIALS, 3, PG III
PASSENGER AIR MAX QUANTITY: 5L **PASSENGER PACKING INSTRUCTION:** 353
CARGO AIR- MAX QUANTITY: 60L **CARGO AIR INSTRUCTION NUMBER:** 364

SECTION 15: REGULATORY INFORMATION

VOC: COMPONENT = 453 gms/Liter

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): REPORTABLE QUANTITY, XYLENE 100 LBS.

SARA TITLE III

SECTION 312 HAZARD CLASS: IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED HEALTH HAZARD; FIRE HAZARD.

SECTION 313 LISTED INGREDIENTS: XYLENE (CAS #001330-20-7),

SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: OCTOBER 10, 2014 **REVISION DATE:** **PREPARED BY:** C.SEM

HAZARD RATING

HMIS: **HEALTH** 3 **FLAMMABILITY** 3 **REACTIVITY** 0

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
 OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
 STEL: SHORT TERM EXPOSURE LIMIT
 TWA: TIME WEIGHTED AVERAGE
 PEL: PERMISSIBLE EXPOSURE LIMIT
 TLV: THRESHOLD LIMIT VALUE
 NA: NOT APPLICABLE
 NE: NOT ESTABLISHED
 ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.